

DEFOAMER WB 500

ENVIRONMENTALLY SAFE WATER BASE DE-FOAMER

- Superior non-polluting water based de-foamer that controls all types of foam in sewage aerators, digesters, scum blankets, cooling towers, industrial cleaning operations, pulp and paper production, and other applications where foaming is a problem.
- Excellent de-foaming in extreme acid or alkaline pH conditions, and is environmentally safe.

SEWAGE PLANTS

For long-term foam control in activated sludge plant, aeration tanks, digesters, sewage entry, or effluent lines. A low viscosity formulation that requires no pre-dilution to achieve complete and rapid foam control. Attach a small valve to the small bung of the de-foamer drum and run a small tubing to the entry fume of the aeration tank or area where foaming of waste occurs. Drip 1 quart to 1 gallon of de-foamer per 10,000 gallons of waste (25-100 PPM) to stop foaming and allow the aerators and digesters to function at maximum capacity and efficiency. For immediate foam relief, over spray the area with a diluted (1-10) of the anti-foam.

INDUSTRIAL CLEANING & WASTE DEFOAMING

Spray or drip small amounts of de-foamer (100-200) into the water-based system to control or eliminate foam. The de-foamer does not affect paper processing, cleaning, cooling tower, or industrial processes. For quick foam knockdown, spray foam with a solution of the de-foamer.

FOR INDUSTRIAL USE ONLY

CAUTION: Keep out of the reach of children. Mild eye irritant. Wash eyes with water until irritation stops. Prolonged contact can irritate the skin. Wash from skin with soap and water. Ingestion in quantity can cause severe diarrhea. Treat as soap ingestion.

EMERGENCY PHONE #: 800-424-9300 / Reference Code: MTEQ / Product Code: 037
REV RAP032609



Maintenance, Equipment & Chemicals, Inc.

1379 Shoemaker St., Nanty Glo, PA 15943
814-749-9015 / 800-831-4963 / Fax 888-536-3795
www.mecchemicals.com mec@mecchemicals.com