

DIELECTRON

HIGH PURITY NONCHLORINATED DIELECTRIC SOLVENT

Exceptionally high purity Isoparaffinic petroleum solvent that is essentially odorless and relatively high boiling. It conforms to Regulation 21 CFR 172.884 as a high purity, odorless, light petroleum hydrocarbon. The high chemical purity, flash over 142°F TCC (also available in 120 & 170 flash points) and high dielectric constant and other attractive properties allow it to be used as a dielectrics solvent.

DIRECTIONS

DO NOT USE NEAR FIRE OR OPEN FLAMES. Always apply from a clean tank by dipping or brushing. Not by spraying or misting. Use the minimum required to do the job. The excess solvent can be wiped off or allowed to evaporate from the clean surface.

SOLVENT RECOVERY & REUSE

For most economical use, recover the spent solvent by distillation. If spent solvent has been used to remove nonvolatile and stable oils, greases, or solid soils, recover by atmospheric distillation. If solvent contains moisture, or non-reactive volatile monomers, or other solvents, you should distill and discard the light ends and keep only the portion distilled between 370-400°F for high dielectric purity. Since flash point is 142°F, DIELECTRON must be distilled with grounded distillation equipment located in an explosive proof area and designed for safe combustible solvent recovery.

INGREDIENTS: Isoparaffinic C8 to C12 hydrocarbon blend. CAS# 67442-47-8.

FOR INDUSTRIAL USE ONLY

CAUTION: Combustible solvent. Do not use near fire or other sources of combustion. Keep out of the reach of children. Do not take internally

EMERGENCY PHONE #: 800-424-9300 / Reference Code: MTEQ / Product Code: 039

MAINTENANCE EQUIPMENT & CHEMICALS, INC.

625 SIMMONS LANE, JOHNSTOWN PA 15909

814-322-1399 / 800-831-4963 / Fax 814-322-3650

www.mecchemicals.com mec@mecchemicals.com