

# SPRAY OFF NF

## HIGH PRESSURE SPRAY CABINET CLEANER OIL SPLITTING-DEFOAMING ACTION-ODORLESS-BIODEGRADABLE

Concentrated, powerful alkaline cleaner formulated for use in high-pressure spray cabinet washers. Non-Foaming superior penetrating power and detergency to remove all types of industrial soils. Powerful emulsifier that forms an unstable emulsion that allows greasy and oily soils to split out of the cleaning solution down to 15 PPM in less than ½ hour and allows solid soils to precipitate. The cleaner is able to be recycled many times for maximum economy in use, while the oils are recovered for disposal. Excellent streak free rinsing to leave a totally clean surface and safe on steel, copper, and their alloys. Upon recycle only a small detergent addition is required to make up for the rinse water dilution of the cleaning solution. Excess cleaning solution that is oil free can be sewerred.

**\*\*\* Do Not Use On Aluminum or Zinc. \*\*\***

### DIRECTIONS

Follow all machine operating instructions. Dilute cleaner with hot or cold water. The cleaner concentration must be determined for the soils being removed that varies with the spray pressure used, spray pattern, cleaning cycle time, and temperature. Usually 1 to 5 ounces per gallon will give superior cleaning on most industrial soils within 1 to 3 minutes. Recommended temperature is 125°F to 200°F. When used at higher temperatures it provides faster cleaning with excellent foam control.

### FOR INDUSTRIAL USE ONLY

**CAUTION:** Keep out of the reach of children. Severe eye irritant. Wash from eyes with water until irritation stops, see a physician immediately. Wash concentrate from hands with water. Wash contaminated clothing before reuse. If mists exceeding 2mg/m<sup>3</sup> or an irritating concentration are inhaled, remove patient to fresh air until respiratory irritation stops. If irritation persists see a physician. Use NIOSH approved respiratory protection until misting stops.

**EMERGENCY PHONE #:** 800-424-9300 / Reference Code: MTEQ / Product Code: 110

**SHIPPING NAME:** Corrosive Liquid NOS (Potassium Hydroxide), Hazard Class: 8, ID#: UN1760, PG: II



Maintenance, Equipment & Chemicals, Inc.

1379 Shoemaker St., Nanty Glo, PA 15943

814-749-9015 / 800-831-4963 / Fax 888-536-3795

[www.mecchemicals.com](http://www.mecchemicals.com) [mec@mecchemicals.com](mailto:mec@mecchemicals.com)